

# 2004 BELL 407

---

SN: 53593 REG: N4WF





Sellacopter™



## 2004 Bell 407

SN: 53593  
REG: N4WF

(512).877.8993  
lan.s@sellacopter.com  
www.sellacopter.com

### AIRFRAME

Airframe Total Time: 2,690.6 hours  
VIP Configured  
No Known Damage History  
N Registered and Ready for US Import

### ENGINE

250-C47B  
Total Time Since New: 2,690.6 hours  
Cycles Since New: 5,022  
Serial No: CAE-847644

### MAINTENANCE

Complete Records Since New  
Detailed Pre-Purchase Inspection Completed  
Full Custom Completion Available After Purchase

### EXTERIOR

White with Red accent  
High Skid Gear  
Crew Step  
Wire Strike Protection System

### INTERIOR

Red Leather  
Four Point Harness (cockpit)  
Dual Controls

### WEIGHTS

Max Take Off Weight: 5,250 Lbs.

\*Specifications and times are subject to verification. Aircraft offered is subject to prior sale, lease, and / or withdrawal from the market.\*



## 2004 Bell 407

SN: 53593  
REG: N4WF

(512).877.8993  
lan.s@sellacopter.com  
www.sellacopter.com

### AVIONICS / INSTRUMENTS

Garmin GTN750Xi COM1/NAV1/GPS1  
Garmin GTN650Xi COM2/NAV2/GPS2  
Garmin GTX335R ADS-B Transponder  
Garmin GMA35R Remote Audio  
Garmin Radar Altimeter  
7 – Seat Intercom System  
MS302 Digital Standby Attitude Indicator  
ELT 406MHZ

### ADDITIONAL EQUIPMENT

19 Gal Aux Fuel Tank  
Air Conditioning  
Wire Strike Protection System  
High Skids with Dual Long Steps  
AAI Deluce Console  
AAI Door Opener Kit  
AAI Wedge Windows  
AAI Shoulder Harness Kit – All Positions  
AAI Maintenance Steps  
Slope Avionics Console  
Ni-Cad Main Battery  
Cabin and Baggage Floor Protector Kit  
Bose Headsets  
Rotor Brake

\*Specifications and times are subject to verification. Aircraft offered is subject to prior sale, lease, and / or withdrawal from the market.\*



  
**Sellacopter™**



APPLY ROTOR BRAKE  
DOVE 40% RPM

407 (S250LB) AIRSPEED LIMITATIONS - KNOTS - IAS

DAT C°	PRESSURE ALTITUDE FT X 1000										
	0	2	4	6	8	10	12	14	16	18	20
52	137										
45	139	132	123								
40	140	133	125	117							
35	140	135	128	118	108						
30	140	137	129	118	108	99					
25	140	138	131	121	109	100	83	86			
20	140	140	133	124	112	102	94	87	80		
0	140	140	140	132	123	111	101	94	86	79	
-25	140	140	140	135	130	125	114	102	95	88	80
-40	137	133	128	123	118	114	110	105	101	93	86

MAXIMUM AUTOROTATION VNE 100 KIAS

407 AIRSPEED LIMITATIONS - KNOTS - IAS

DAT C°	PRESSURE ALTITUDE FT X 1000										
	0	2	4	6	8	10	12	14	16	18	20
52	137										
40	139	132	123								
35	140	133	125	117							
30	140	135	128	118	108						
25	140	137	129	118	108	99					
20	140	138	131	121	109	100	83	86			
0	140	140	140	132	123	111	101	94	86	79	
-25	140	140	140	135	130	125	114	102	95	88	80
-40	137	133	128	123	118	114	110	105	101	93	86

MAXIMUM AUTOROTATION VNE 100 KIAS

Panel of electrical switches and controls, including master battery disconnect, fuel pump, and other aircraft systems.

Panel of flight controls, including throttle levers, mixture controls, and other engine-related switches.





TAKE OFF AND LANDING  
HEAD MUST BE UP IN  
UP POSITION





TAKE OFF AND LANDING  
HEAD REST MUST BE IN  
UP POSITION

DANGER  
TAIL ROTOR



Sellacopter™



FUEL  
FUEL SYSTEM USABLE CAPACITY  
BASIC AIRCRAFT 127 U.S. GALLONS - 483 LITERS  
WITH 487-704-811 AUX KIT 147 U.S. GALLONS - 559 LITERS  
SEE FLIGHT MANUAL FOR APPROVED FUELS



CAUTION  
INLET STRAPSET MUST COVER, AUTO  
DOWN AND BEG FIRST AID KIT MUST BE  
IN EXTENSION AREA WITH SNAP ON  
INSTALLER. REDUCE MAXIMUM ALLOW  
BAGGAGE COMPARTMENT WEIGHT & POS



  
**Sellacopter™**



  
**Sellacopter™**



1-855-SELLACOPTER (735-5226)

[Sales@sellacopter.com](mailto:Sales@sellacopter.com)

[Sellacopter.com](http://Sellacopter.com)