

# 2014 BELL 407GX

---

SN: 54527 REG: N409SK











## 2014 Bell 407GX

SN: 54527

REG: N409SK

(512).877.8993

lan.s@sellacopter.com

www.sellacopter.com

### AIRFRAME

Airframe Total Time: 3,688.8 hours

Two Owners Since New

USA Based and N Registered

No Known Damage History

Utility / Aerial Survey Use

### ENGINE

RR 250-C47B

Total Time Since New: 3,688.8 hours

Cycles Since New: 3,376

Serial No:CAE-848698

### MAINTENANCE

Complete Records Since New

Fresh 12 Month Inspection: April 2025

Fresh 300 HR Inspection: 3,688.8 hours

Current Maintenance Provider: AHS

### EXTERIOR

Blue and White

Black and Silver Accent Stripes

High Visibility Doors (Cockpit)

High Skid Gear

Crew Step

### INTERIOR

Black Cloth

Four Point Harness (cockpit)

Dual Controls

Litter Door (Aft Left Passenger)

### WEIGHTS

Max Take Off Weight: 5,250 Lbs.

\*Specifications and times are subject to verification. Aircraft offered is subject to prior sale, lease, and / or withdrawal from the market.\*



## 2014 Bell 407GX

SN: 54527

REG: N409SK

(512).877.8993  
lan.s@sellacopter.com  
www.sellacopter.com

### AVIONICS / INSTRUMENTS

GDU 1040H Display

GDC 74H Air Data

GRS 77H ADAHRS

ACP53 Audio Panel

GIA 63H VHF Radio (x2)

GTX-69 transceiver

GTS 800 TAS Processor

ELT

### ADDITIONAL EQUIPMENT

High Visibility Doors (Cockpit)

Tail Rotor (Rear View) Camera

Aux Fuel Tank

Engine AFS Barrier Filter

Air Conditioning

Headliner with ECS Ducts

PreFlight Steps

Wire Strike Protection System

**\*All equipment in the current equipment list from “Wysong Enterprises Installation” and below will be removed, and NOT included in sale.**

\*Specifications and times are subject to verification. Aircraft offered is subject to prior sale, lease, and / or withdrawal from the market.\*









  
**Sellacopter™**





407 AIRSPEED LIMITATIONS - KNOTS - IAS													407 (5250LB) AIRSPEED LIMITATIONS - KNOTS - IAS												
PRESSURE ALTITUDE FT X 1000													PRESSURE ALTITUDE FT X 1000												
OAT °C	0	2	4	6	8	10	12	14	16	18	20		OAT °C	0	2	4	6	8	10	12	14	16	18	20	
52	137												52	137											
45	130	132	125	119									45	130	132	125	119								
40	140	133	126	119	113								40	140	133	126	119	113							
35	140	135	128	120	113	106							35	140	135	128	120	113	106						
30	140	137	129	122	115	108	102	95	89				30	140	137	129	122	115	108	102	95	89			
25	140	138	131	124	116	109	102	95	88				25	140	138	131	124	116	109	102	95	88			
20	140	140	133	125	117	110	103	95	88				20	140	140	133	125	117	110	103	95	88			
15	140	140	140	132	123	115	107	100	92				15	140	140	140	132	123	115	107	100	92			
10	140	140	140	140	132	123	115	107	100				10	140	140	140	140	132	123	115	107	100			
5	140	140	140	140	140	132	123	115	107				5	140	140	140	140	140	132	123	115	107			
0	140	140	140	140	140	140	132	123	115				0	140	140	140	140	140	140	132	123	115			
-5	140	140	140	140	140	140	140	132	123				-5	140	140	140	140	140	140	140	132	123			
-10	137	133	128	123	118	114	109	104	97				-10	137	133	128	123	118	114	109	104	97			
MAXIMUM AUTOROTATION VNE 100 KIAS													MAXIMUM AUTOROTATION VNE 100 KIAS												









MAXIMUM ALLOWABLE WEIGHT 250 LBS  
MAXIMUM ALLOWABLE WEIGHT PER SQ. FT. 6 LBS  
CARGO MUST BE SECURED  
IN ACCORDANCE WITH  
FLIGHT MANUAL INSTR.





  
**Sellacopter™**





  
**Sellacopter™**





  
**Sellacopter™**









  
**Sellacopter™**









1-855-SELLACOPTER (735-5226)

[Sales@sellacopter.com](mailto:Sales@sellacopter.com)

[Sellacopter.com](http://Sellacopter.com)